



Sartocon® Slice 200 Stainless Steel Holder

Low hold-up volume Crossflow holder for Sartocon® Slice 200 cassettes

Crossflow Holder



Feature	Benefits
Vertical position	self draining self venting
Low hold up volume	minimized working volume
Female Luer lock threads	safe fit of the adapters
Small footprint	compact system
Unique optimized In- and Outlets	no air lock
Adjustable feet	secure stand
Fits up to two Slice 200 cassettes	high flexibility for up to 5 l working volume

Specifications

Materials of Construction

Filterplate	316L (1.4404 1.4435) Stainless steel
Connectors	female luer lock threads, 316L (1.4404 1.4435) Stainless steel
O-Ring	Silicone
Nuts for tie rods	Nickel coated bronze
Feet	Polyethylene
Other components	316L (1.4404 1.4435) Stainless steel

Description

Sartocon® Slice 200 Holder

The Sartocon® Slice 200 stainless steel holder is optimized for the use with up to two Slice 200 Crossflow cassettes (max. 0.04 m²). It is designed for low volume applications from 20 ml to 5 l.

Target use:

- scaling studies
- product discovery
- pre-clinical trials
- small pilot lots

Sartocon® Slice 200 cassettes with a filter area of 200 cm² each, are available with Hydrosart and Polyethersulfone membrane types.

The Sartocon® Slice 200 system covers the whole range of pharmaceutical and biotechnological crossflow applications like concentration and diafiltration of proteins, vaccines, viruses, antibodies, oligo nucleotides, endotoxin removal etc. The system is suitable for cell harvesting and clarification processes.

The family of Sartorius Stedim Biotech Crossflow holders feature the latest advances in crossflow design:

- vertical orientation
- self draining systems
- low minimal hold-up volumes

The Sartocon® Slice 200 cassette (filter area: 200 cm²) has the same hydrodynamic flow path design and identical materials like the larger Sartocon® Slice (0.1 m²) and production scale Sartocon® Cassettes (0.6 or 0.7 m²). This uniform design within the Sartocon® family provides the user with predictable performance for scaling studies. The Slice 200 holder completes the Slice 200 cassette in an ideal way and gives the perfect tool for every low volume crossflow application.

The Slice 200 holder uses female stainless steel Luer lock connectors. This ensures a safe and reliable connection to additional equipment. The stainless steel luer lock thread allows the use of even polypropylene adapters without the risk of damaging. The feed and retentate ports as well as the two filtrate ports are located each on one side of the holder. This allows, together with the small footprint design, a compact system with low minimum working volume. The adjustable feet guarantees a firm stand of the holder on the bench.

The bores of the ports are widened up to the cassettes side, to avoid air locks and to ensure a proper cleaning in place behaviour of the Slice 200 system.

Technical Data

Holder Hold-up volume Feed Retentate ports	<2 ml
Holder Hold-up volume permeate ports	<2 ml
Maximum number of cassettes	2 Slice 200 cassettes (200 cm ² each)
Dimensions (L×W×H)	160×120×275 mm
Weight	5.8 kg

Accessories and Ordering Informations:

Slice200 stainless steel holder	17525--01
Pressure gauge, 0-6 bar, oil damped	17525---001
SARTOFLOW [®] Slice 200 benchtop system (240V)	17525SYS-BT2
SARTOFLOW [®] Slice 200 benchtop system (120V)	17525SYS-BT1

Ordering Information

Available Slice 200 types and order numbers

Ultrafiltration Cassettes 200 cm²

Membrane	MWCO	Order Numbers Sartocon [®] Slice 200
PESU	1 kD	308 146 09 02 E--SW
	5 kD	308 146 29 02 E--SW
	8 kD	308 146 34 02 E--SW
	10 kD	308 146 39 02 E--SW
	30 kD	308 146 59 02 E--SW
	50 kD	308 146 50 02 E--SW
	100 kD	308 146 68 02 E--SW
Hydrosart [®]	300 kD	308 146 79 02 E--SW
	2 kD	308 144 19 02 E--SW
	5 kD	308 144 29 02 E--SW
	10 kD	308 144 39 02 E--SW
	30 kD	308 144 59 02 E--SW
100 kD	308 144 68 02 E--SW	

Microfiltration Cassettes 200 cm²

Membrane	Pore Size	Order Numbers Sartocon [®] Slice 200
PESU	0.1 µm	308 154 58 02 W--SW
Hydrosart [®]	0.2 µm	308 186 07 02 W--SW
	0.45 µm	308 186 06 02 W--SW

The preservation liquid is either 20% Ethanol or Glycerin.

Sartorius Stedim Biotech GmbH
August-Spindler-Strasse 11
37079 Goettingen, Germany

Phone +49.551.308.0
Fax +49.551.308.3289
www.sartorius-stedim.com

USA Toll-Free +1.800.368.7178
UK +44.1372.737159
France +33.442.845600
Italy +39.055.63.40.41
Spain +34.90.2110935
Russian Federation +7.812.327.5.327
Japan +81.3.4331.4300

Specifications subject to change
without notice. Printed and copyrighted
by Sartorius Stedim Biotech GmbH. | W
Publication No.: SPC2039-e140303
Order No.: 85030-519-23
Ver. 03 | 2014